

| SADPA RIFLE / CARBINE CLASSIFIER 2024 | | | |
|---------------------------------------|--|--------------------|-----------------|
| Scoring | Limited | | |
| Round Count | 20 for SLR: (Self Loading Rifle), 10 for MAR: (Manual Action Rifle). | | |
| Concealment | Optional | Rules | SADPA 2024 V2.5 |
| Targets | 2 x SADPA Paper Targets | | |
| Start Signal | Timer | Stop Signal | Last Shot Fired |
| Muzzle Safe | 180° Degree Rule | | |

| CLASSIFIER STRINGS | | | | | |
|--------------------|------------|------------|----------------|--|--|
| String | Rounds SLR | Rounds MAR | Start Position | Start Condition | Procedure |
| 1 | 4 | 2 | SP1 | Standing upright, with firearm in ready position, loaded with SLR: four rounds MAR: two rounds chamber empty (action must be closed and hammer down). | On start signal, load and engage all targets SLR: with two rounds each to the head MAR: with one round each to the head |
| 2 | 4 | 2 | SP1 | Standing upright, with firearm in the ready position, loaded with SLR: two rounds MAR: one round | On start signal, engage all targets, SLR: with two rounds each, MAR: with one round each, reloading, when necessary. |
| 3 | 4 | 2 | SP2 | Standing upright, with firearm loaded and in ready position. Shooter may start at either of the SP2 positions. | On start signal, engage the target directly in front of the chosen SP2 position with SLR: two rounds, MAR: one round Move to opposite SP2, engage the other target with SLR: two rounds, MAR: one round |
| 4 | 4 | 2 | SP3 | Standing upright with one's back to targets, firearm unloaded on the drum. Actions closed, hammer down. All loading devices/ammunition on drum. | On start signal, turn and whilst remaining standing, load and engage all targets with SLR: two rounds each, MAR: one round each |
| 5 | 4 | 2 | SP3 | Standing upright, with firearm loaded and in ready position. | On start signal, engage all targets from around low cover with SLR: two rounds each, MAR: one round each. |

| CLASSIFIER TIMES | | | | | |
|---|--------|--------|--------------|----------|--------|
| Division | Master | Expert | Sharpshooter | Marksman | Novice |
| Enhanced Service Rifle (ESR) Stock Service Rifle (SSR) | < 26 | < 35 | < 46 | < 57 | ≥ 57 |
| Open Rifle (OR) Pistol Calibre Carbine (PCC) | < 24 | < 33 | < 44 | < 55 | ≥ 55 |
| Rimfire (22R) | < 23 | < 32 | < 43 | < 54 | ≥ 54 |
| Manual-Action Small Rifle (MASR) | < 28 | < 36 | < 47 | < 58 | ≥ 58 |
| Manual-Action Large Rifle (MALR) | < 30 | < 40 | < 51 | < 62 | ≥ 62 |

| STAGE BUILDING NOTES |
|---|
| 1. Targets must be positioned so that the topmost point of the target is 1.5m ± 0.1m above the ground. 2. The distance between targets is 3m +0.1m, -0m measured between the inside edges of the targets. |

STAGE BUILDING NOTES

3. Red lines indicate the fault lines to be used. The fault line must be aligned from the edge of the drum to the center of the targets as indicated. The fault line may not extend more than 1m +0m, -0.1m past the rear edge of the drum.
4. SP1 indicate a shooting box that measures 1x1m ± 0.2m where the front edge of the box is aligned with the 5m +0.1m, -0m mark.
5. SP2 indicates shooting boxes that measure 1x1m ± 0.2m where the front edges of the boxes are aligned with the 10m +0.1m, -0m mark and the distance between the inner edges of the boxes is 5m +0.1m, -0m.
6. SP3 is a similar shooting box behind a drum where the rear edge of the drum is at the 15m +0.1m, -0m mark.

